

## FEATURES:

- Wireless Transceiver for Cypress wireless system
- Used in conjunction with WGR-110-900-2-RK for wireless range testing
- Transmission distance 200 to 300 ft in typical industrial sites
- Wireless “Star” topology does not require repeaters



## KEY PRODUCT SPECIFICATIONS

Power:	100-240 VAC, 0.6 Amps max
Operating Frequency:	915 MHz ISM Band
Operating Condition:	-30°C to +70°C; 95% RH Max, Noncondensing
Storage Condition:	-40°C to +85°C; 90% RH Max, Noncondensing
Product Weight:	16.0 oz (454 grams)
Dimensions (L x W x H):	6.35" x 4.23" x 1.69" (161.3 mm x 107.4 mm x 42.8 mm)
Certifications:	US FCC and Canada IC Listed

## ORDERING INFORMATION

MODEL	DESCRIPTION
IND-Hub-900-RT	Industrial Hub LoRaWAN for Range Test

### HEADQUARTERS

5883 Rue Ferrari, Suite 100  
 San Jose, CA 95138  
 +1 800 544-5411  
[www.CypressEnviroSystems.com](http://www.CypressEnviroSystems.com)  
[info@CypressEnviroSystems.com](mailto:info@CypressEnviroSystems.com)

Cypress EnviroSystems and its logo are trademarks of Cypress EnviroSystems, Inc. The name of any other company, products, or services mentioned herein are for identification purposes only and may be trademarks or service marks of or may be copyrighted by their respective holders.