

## FEATURES:

- Retrofit existing pneumatic thermostats in minutes
- Delivers DDC functionality
- Remote monitoring of branch pressure
- Remote control of setpoint
- Automatic self-calibration
- Occupancy override notification
- Programmable temperature setbacks
- Easy to install wireless system
- Built-in BACnet/IP interface to integrate with existing building automation systems



## Plug and Play Wireless Pneumatic Thermostat (WPT) replaces existing Siemens, Honeywell, Johnson, Robertshaw units in minutes

The patented Wireless Pneumatic Thermostat (WPT) delivers DDC functionality at a fraction of the time and cost without the need to change out pneumatic pipes, run wires, replace actuators or disturb occupants. Not necessary to upgrade the entire building at one time; may selectively retrofit individual thermostats for incremental benefits:


- Separate setpoint control for heating and cooling
- Automatic setpoint changes based on time-of-day schedule and night setback
- Automatic calibration
- Notification on occupancy override
- Early problem detection to avoid occupant complaints
- Zone control for optimal energy use and comfort
- System can work standalone or integrated with existing Building Automation System (BAS) via BACnet/IP

Saves energy, improves comfort for occupants, and lowers maintenance cost of legacy pneumatic HVAC systems.

## BENEFITS:

- Separate heating and cooling setpoint control with adjustable deadband
- Digital zone control optimizes energy usage and comfort
- Programmable temperature setbacks save energy
- Enables use for utility demand response programs
- Occupancy override logs tenant after-hours usage
- Diagnostic monitoring reduces maintenance and operating cost

## WPT SYSTEM ARCHITECTURE



## KEY PRODUCT SPECIFICATIONS:

|                                     |  |
|-------------------------------------|--|
| <b>Action:</b>                      | Direct / Reverse Acting  |
| <b>Number of Pipes:</b>             | Single / Dual Pipe   |
| <b>Setpoint Temperature Range:</b>  | 55°F to 85°F (13°C to 29°C)  |
| <b>Deadband Pressure:</b>           | User adjustable. Default 8 psig +/- 1 psi                                |
| <b>Deadband Range:</b>              | 0°F (no deadband) to 20°F (11 °C)  |
| <b>Air Connections:</b>             | 3/32" (2.5 mm) ID tube fittings  |
| <b>Max Pipe Operating Pressure:</b> | 25 psi (170 kPa)   |
| <b>Airflow Usage:</b>               | 0.011 scfm (5.2 mL/s) maximum  |
| <b>Sensitivity:</b>                 | Factory adjusted to 2.0 – 2.5 psi/F                                      |
| <b>Sensor Accuracy:</b>             | +/- 0.7°F (0.4°C) for temperature  |
| <b>Operating Frequency Band:</b>    | 2.4 GHz ISM Band   |
| <b>Battery Life:</b>                | More than two years with 4 setpoint changes per day                      |
| <b>Operating Condition:</b>         | 32°F to 122°F (0°C to 50 °C); 95% RH Maximum, Noncondensing              |
| <b>Storage Condition:</b>           | -40°F to 122°F (-40°C to 50 °C); 95% RH Maximum, Noncondensing           |
| <b>Dimensions:</b>                  | Length – 5.6 in (141mm) Width – 4.1 in (103.5mm) Depth – 2.1 in (53.3mm) |

## OUR FAMILY OF PRODUCTS:

|   |   |   |   |   |
|---|---|---|---|---|
|  |  |  |  |  |
| <b>WIRELESS PNEUMATIC THERMOSTAT (WPT)</b>  | <b>WIRELESS STEAM TRAP MONITOR (WSTM)</b>   | <b>WIRELESS GAUGE READER (WGR)</b>  | <b>WIRELESS TRANSDUCER READER (WTR)</b>   | <b>WIRELESS FREEZER MONITOR (WFM)</b>   |

### HEADQUARTERS

5883 Rue Ferrari, Suite 100

San Jose, CA 95138

+1 800 544-5411

[www.CypressEnviroSystems.com](http://www.CypressEnviroSystems.com)

[info@CypressEnviroSystems.com](mailto:info@CypressEnviroSystems.com)

Cypress EnviroSystems and its logo are trademarks of Cypress EnviroSystems, Inc. The name of any other company, products, or services mentioned herein are for identification purposes only and may be trademarks or service marks of or may be copyrighted by their respective holders.