Install Readme

You have two options to connect to the BBS:

- 1. Connect a monitor, keyboard and mouse directly to the BBS
- 2. The Windows login is either Username: User with no password or Username: wgrag Password: systems (depending on the version of the BBS)

OR

- 1. Using VNC from your laptop. You will need VNC Viewer in order to log directly onto the Blue Box remotely. VNC Viewer can be downloaded here (It's free): http://www.realvnc.com/products/free/4.1/download.html.
- 2. To connect to the BBS using VNC Viewer, Use the Computer name WGRServerXXX (which is on a label on the bottom of the Blue Box) as Host and depending on the version of your system, either "cypress" or "systems" as the VNC password
- 3. You can either connected your laptop directly to the Blue Box via a network cable connected to either port on the back of the BBS, Or If the Blue Box is connected to the same LAN as your laptop, you can access it via VNC without having to connect your laptop directly to the network port on the Blue Box.
- 3. The Windows login is either Username: User with no password or Username: wgrag Password: systems (depending on the version of the BBS)

Install Steps:

- 1. It is very important to have the latest Window's Updates before installing version 4.0, so verify that you have an internet connection, and open up internet explorer, click "Tools" and click "Windows Update". Follow the instructions to download all the latest Window's Patches
- 2. Unzip by right clicking the .zip file and selecting "Extract All"
- 3. From the extracted files goto: ServerUpgrade/batfiles/
- 4. Double Click UpgradeServer.cmd
- 5. A command window will launch performing the upgrade **DO NOT CLOSE THIS WINDOW** it will automatically close when the update is complete

Configuring the BBS to work with multiple products:

- 1. Launch the web console either from your PC or directly from the BBS
- 2. In the address bar, type http://WGRServerXXX/wgrwebapp/admin.aspx
- 3. Select the devices that will talk to this BBS in the "Configure Device" area, and click "Update Site Devices" (see example below)

