

## FEATURES:

- Non-invasive, easy clamp on fit. No need to break seals.
- Available adapters to fit most panel indicators.
- Uses 900MHz LoRa compliant radio communications .
- Battery life up to three years on 15 minute sample rate.
- Low Battery indicator.
- NEMA4/IP66 enclosure for indoor/outdoor use.
- One-time calibration and setup.
- No new software to install – data can be view through standard browser (requires Green Box Controller).
- FCC, ROHS Compliant.
- Optional connectivity to existing plant or building automation systems via OPC, RESTful API, or BACnet/IP.
- Includes quick disconnect feature to allow unit to be removed and reattached without recalibration.



**Non-invasively read mechanical odometers and/or LED/LCD numeric indicators and wirelessly transmit the data to a PC, data acquisition or automation system.**

The patented Wireless Digit Reader (WDR) requires a fraction of the cost and time of installing conventional transducers or transmitters. It does not require the removal of old indicators, learning new software, or disruption of plant processes.

Just clamp it on to an existing indicator and, in minutes, wirelessly acquire readings on an existing data acquisition or control system.

## KEY PRODUCT SPECIFICATIONS:

<b>Indicator Compatibility:</b>	Most indicators from 1.7" to 4.64" width
<b>Data Capture Rate:</b>	User selectable from five second to 18 hour sample rate
<b>Wireless Frequency:</b>	902.000 MHz to 928.000 MHz
<b>Wireless Range:</b>	500 to 1,500 ft in typical plant environments
<b>Modulation Method:</b>	FSK, GFSK, and LoRa® Technology modulation
<b>Approvals:</b>	FCC CFR47, Part 15 Subpart C
<b>Power Supply:</b>	Two 3V lithium batteries, type CR123A
<b>Battery Life:</b>	>1 year at 5 minute sample rate, >3 years at 1 hour sample rate
<b>Vibration:</b>	Up to 4G RMS
<b>Humidity:</b>	10-99% RH, non-condensing
<b>Operating Temperature:</b>	-4°F to 158°F (-20°C to 70°C)
<b>Storage Temperature:</b>	-40°F to 176°F (-40°C to 80°C)
<b>Enclosure:</b>	NEMA 4X, IP66 compliant (outdoor, water resistant)
<b>Housing Material:</b>	ABS with UV inhibitors
<b>Display:</b>	LCD display (not backlit) for manual reading
<b>Dimensions:</b>	2.6" x 2.6" x 1.3"
<b>Weight:</b>	0.33 lbs including batteries

### HEADQUARTERS

6830 via del Oro, Suite 100  
 San Jose, CA 95119  
 +1 800 544-5411  
[www.CypressEnviroSystems.com](http://www.CypressEnviroSystems.com)  
[info@CypressEnviroSystems.com](mailto:info@CypressEnviroSystems.com)

Cypress EnviroSystems and its logo are trademarks of Cypress EnviroSystems, Inc. The name of any other company, products, or services mentioned herein are for identification purposes only and may be trademarks or service marks of or may be copyrighted by their respective holders.